

## Rotary Expander System Features



Front View

- High-speed unit assembles ExpandOS™ to meet any speed or volume requirements.
- Can be easily integrated with hoppers, automation or baggers or can be used as a stand-alone unit.
- Height adjustable with several options for stand-alone use.
- Dispensing chute can be customized to any application.

### ROTARY EXPANDER SYSTEM SPECIFICATIONS

Power: 115V, 60Hz, Single-Phase, 5 Amp

Output: 9.6 Cu Ft / Minute

Weight: 250 lbs.

Foot Print (Standard Stand): 52.5 x 52.5

Max. Height: Stand 72", Rotar, Expander 33.5

## Standard Expander System Features



Front View

Side View  
Packing Platform Installed

- All-in-one solution for **efficient** and **effective** packaging utilizing the **superior protection** of the **eco-friendly** ExpandOS™ packaging product.
- The standard Expander System is **adaptable**, **adjustable** and **mobile** to fit into practically any packing environment for use with any size container. Its features include additional paper storage, securely locking casters, an adjustable packing platform, and a 1½ Cu-Ft capacity dispensing hopper.
- **User friendly** and **easy to use** control interface features a fully digital message and status display as well as height adjustment and emergency shutoff controls giving the operator complete control over the Expander System's operation.
- Adjustable height of the dispensing hopper and packaging platform makes the Standard Expander System **ergonomically friendly** to each operator while accommodating any container size.

### STANDARD EXPANDER SYSTEM SPECIFICATIONS

Power: 115V, 60Hz single-phase, 3 Amp

Output of product/min: 1.75 Cu Ft / Minute

Weight: 365 lbs. (complete system)

Foot Print: 39" x 37.1"

Working Height: 89"

Contact us today to find out how  
ExpandOS™ can work for you!

Phone: (303) 329-8477  
Toll Free: 1 (866) 909-6266  
Email: [Office@expandos.com](mailto:Office@expandos.com)  
Website: [www.expandos.com](http://www.expandos.com)